


# SUPABORD EDGE TAPE

## SPECIFICATION SHEET



### DESCRIPTION

SupaBord Edge Tape is one of two tapes in the SupaBord product range.

SupaBord Edge Tape is specifically designed to secure SupaBord Temporary Floor Protection to floors and walls for up to 45 days. SupaBord Edge Tape is made from quality crepe paper with a natural rubber adhesive to provide instant attachment to a wide variety of surfaces.

### FEATURES

- Joins SupaBord Temporary Floor Protection edges to surfaces
- Strong and flexible
- Low to medium 45-day contractor grade adhesive
- Convenient size 40mm wide x 30m long x 0.12mm thick

### INSTALLATION INSTRUCTIONS

1. Peel back the edge of **SupaBord Edge Tape** and begin to unroll
2. Tape the SupaBord edges to the floor with **SupaBord Edge Tape**
3. Simultaneously apply firm pressure and smooth down the tape
4. Carefully cut the end with a utility knife
5. When finished, fold the edge of the tape back against the roll to use at a later time
6. To remove, roll up tape and discard




**SupaBord**  
Bord Industries HK Ltd  
Suite 1106-8, 11/F, Tai Yau Building,  
181 Johnston Road, Wanchai, Hong Kong  
technical@supabord.com www.supabord.com



# SUPABORD EDGE TAPE

## MATERIAL SAFETY DATA SHEET



### PRODUCT & COMPANY IDENTIFICATION

**Distributor Name:**  
Bord Industries HK Ltd  
Suite 1106-8, 11/F, Tai Yau Building,  
181 Johnston Road, Wanchai, Hong Kong

**Product information contact:**  
technical@supabord.com

**MSDS information contact:**  
technical@supabord.com

**Product name:** SupaBord Edge Tape

**Issue Date:** June 2016

### PRODUCT SPECIFICATIONS

Total thickness	0.12mm
Backing	Crepe Paper
Adhesive type	Rubber and solvent based
Adhesion to steel	27N/100mm
Tensile Strength MD	333N/100mm
Backing Weight	58g/m <sup>2</sup>
Temperature (ideal)	21° Celsius (70° Fahrenheit)
Humidity (ideal)	50%
Elongation	7%
Chemical Family	Saturated paper backing, natural rubber and resins solvent based adhesive
Trade Name	SupaBord Edge Tape
Material Use	Light to medium duty tape

### AVAILABLE SIZE

**Colour:** White **Roll Weight:** 150g

**Roll Size:** 40mm wide x 30m long x 0.12mm thick

### HANDLING AND STORAGE

We recommend safe storage in a cool, dry place.

Store at room temperature from 15° to 25° Celsius (59° to 77° Fahrenheit) with a maximum humidity of 65%. Keep out of direct sunlight exposure. Product shelf life and storage is 12 months. If SupaBord Edge Tape is stored in extreme conditions over 35° Celsius (95° Fahrenheit) or below 4.5° Celsius (40° Fahrenheit), allow the product to return to room temperature prior to use.

Like most tapes, avoid taping directly to finished surfaces. We recommend undertaking a sample test on the curing floors prior to use.

### USES

SupaBord Edge Tape is specifically designed to secure SupaBord Temporary Floor Protection to floors and walls for up to 45 days. SupaBord Edge Tape is made from quality crepe paper with a natural rubber adhesive to provide instant attachment to a wide variety of surfaces.

### DISCLAIMER

Reasonable care has been taken in preparation of this document. The information in this document was obtained from sources, which we believe reliable. Bord Industries HK Ltd extends no warranties and makes no representations as to the expressed or implied accuracy or completeness of the information contained therein. We do not assume or accept responsibility for loss, damage or expense in any way connected with the handling, storage, use or disposal of the product. We disclaim all liability for any harmful health effects, which may be caused by misuse of our products.

© 2011 SupaBord, Bord Industries HK Ltd. All rights reserved for product names and attributes registered.

### SAFETY

#### Hazard Identification

#### Eye Contact:

Eye contact is not expected during normal use. Eye irritation including redness, cornea scratching and tearing may occur.

#### First Aid Measure:

Immediately flush eyes with large amounts of water. In the case of an emergency, seek immediate medical attention.

#### Fire Fighting Measures

#### Extinguishing Methods:

Water spray, Carbon Dioxide, dry power agent

#### Special Procedures:

Full protective equipment and self-contained breathing apparatus

#### Exposure Controls

**Eye Protection:** Avoid eye contact

**Ventilation:** Ventilated environment

**Fire and Explosion Avoidance:** Avoid flames

#### Physical and Chemical Properties

**Appearance:** Solid, white

**Flammability:** Combustible

**Water Vapour Transmission:** Permeability not less than 500g/m<sup>2</sup>

